



Construction Galvanized Steel H Beam In H Shape Cross Section 5-34mm Flange 50-400mm

Our Product Introduction

for more products please visit us on galvmetal.com

Basic Information

- Place of Origin: Hebei, China
- Certification: ISO9001
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: According to customer needs
- Delivery Time: 15-30 work days
- Payment Terms: TT



Product Specification

- Size: Customization
- Flange Width: 50-400mm
- Surface Treatment: Galvanized, Painted, Or As Required
- Length: 6-12m
- Material: Carbon Steel
- Packing: In Bundles Or As Required
- Shape: H-shaped Cross-section
- Thickness: 5-34mm
- Theoretical Weight: 56.7kg/m
- Highlight: **construction galvanized steel h beam ,
construction galvanized h beam ,
34mm galvanized h beam**



More Images



Product Description

Product Description:

One of the key advantages of our H-beam product is its shape. The H-shaped cross-section provides excellent resistance to bending and twisting forces, making it a popular choice for load-bearing structures such as bridges, buildings, and towers. The H-beam is also easy to fabricate and weld, making it a versatile option for a wide range of construction and engineering applications.

In addition to its strength and durability, our H-beam product also offers a range of surface treatments. We offer galvanized and painted options, as well as customized surface treatments to meet your specific requirements. These treatments help to protect the H-beam from corrosion and other forms of wear and tear, ensuring that it remains strong and durable for years to come.

Overall, our H-sectional beam product is a high-quality, versatile, and cost-effective option for a wide range of construction and engineering applications. With its excellent strength, durability, and range of available surface treatments, it is an ideal choice for load-bearing structures of all kinds.

Features:

Product Name: H-Beam

Surface Treatment: Galvanized, Painted, Or As Required

Grade: Q235B, Q345B, SS400, A36, A572 Gr50, S235JR, S355JR

Application: Construction, Bridge, Machinery, Equipment Foundation, Support, Etc.

Thickness: 5-34mm

Shape: H-shaped Cross-section

This product is a type of **structural steel I beam**, also known as an **H sectional beam** or **sectional steel beam**.

Technical Parameters:

Technical Parameter	Value
Product Name	H Beam, H Sectional Beam
Material	Carbon Steel
Grade	Q235B, Q345B, SS400, A36, A572 Gr50, S235JR, S355JR
Flange Width	50-400mm
Flange Thickness	7-34mm
Thickness	5-34mm
Length	6-12m
Application	Construction, Bridge, Machinery, Equipment Foundation, Support, Etc.
Surface Treatment	Galvanized, Painted, Or As Required
Packing	In Bundles Or As Required
Shape	H-shaped Cross-section

Applications:

With its H-shaped cross-section, H Beam is widely used in various construction scenarios like bridges, machinery, equipment foundations, supports and more. It has a length of 6-12m and is packed in bundles or as required. The flange thickness ranges from 7-34mm.

H Beam has a diverse range of application occasions and scenarios. It is commonly used in the construction of buildings, factories, and bridges. It is also used in the manufacturing of heavy machinery and equipment foundations. H Beam is a reliable and sturdy product that can withstand heavy loads and pressure.

Its robustness and durability make it suitable for use in harsh environments like mining, oil drilling, and construction sites. H Beam's unique structural design makes it an ideal choice for applications requiring high strength and stability.

In conclusion, H Beam is a versatile and reliable product that can be customized according to customer requirements. Its diverse range of applications makes it an indispensable product in the manufacturing and construction industries.



Packing and Shipping:

Product Packaging:

The H-Beam product will be packaged securely with protective materials to ensure safe transportation. It will be wrapped in plastic and placed on a pallet for easy handling. The dimensions of the package will be 6 meters in length, 30 centimeters in width, and 30 centimeters in height.

Shipping:

The H-Beam product will be shipped via a freight carrier. The cost of shipping will depend on the destination and weight of the package. The estimated delivery time will be provided upon purchase and may vary based on the location.

FAQ:

Q: What is the place of origin for the H-Beam product?

A: The place of origin for the H-Beam product is Hebei, China.

Q: What certification does the H-Beam product have?

A: The H-Beam product is certified with ISO9001.

Q: What is the minimum order quantity for the H-Beam product?

A: The minimum order quantity for the H-Beam product is negotiable.

Q: What is the price of the H-Beam product?

A: The price of the H-Beam product is negotiable.

Q: How is the H-Beam product packaged and what is the delivery time?

A: The packaging details for the H-Beam product are according to customer needs and the delivery time is 15-30 work days.

Q: What are the payment terms for the H-Beam product?

A: The payment terms for the H-Beam product are TT.



Tianjin Baoli Gold Pipe Co., Ltd



+86-15022596169



tjbaolijin@126.com



galvmetal.com

Jinghai District, Tianjin City, China